


INSTALLATION GUIDELINES and GENERAL INFORMATION:

1. All low voltage wiring is #22 AWG, unless otherwise noted.
3. All OPTIONAL wiring is shown in dotted lines.
2. Observe all local and national electrical and building codes.
4. All terminals connections shown may not be in the order that they appear on the equipment.
5. Below the amplifier board you can install an OPTIONAL model# BEC-3 button illuminator board. This board has Yellow LED's and two (2) screw terminals marked '8' and 'O'. If you wish to illuminate the door station button(s), provide a separate 8VAC power source (transformer) to these two (2) screw terminals (polarity not important).

 <p>42 Central Drive, Farmingdale NY 11735-1202 (631) 777-5500 Fax: (631) 777-5599 TOLL-FREE Technical Line 1-800-666-4800 Email: info@alpha-comm.com</p>	<p>TYPICAL WIRING DIAGRAM FOR S.T.R™ DPK2W-3C Intercom Kit (2-wire)</p> <p>With 3- Inside handsets and a 3-button compact surface door station, with built-in system intercom amplifier.</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------